

ALUMINIUM FLEXIBLE HOSE

TECHNICAL DATA SHEET

APPLICATION

The Aluminium Flexible Hose is a range of fully flexible uninsulated aluminium/polyester laminated ducting, which has been specially designed for Domus Ventilation. Due to its flexibility it is easy to connect to either round or oval ducting.

CONSTRUCTION

The Domus Ventilation Aluminium Flexible Hose is multiply reinforced aluminium and polyester laminated ducting with an encapsulated high tensile steel wire helix.



ADVANTAGES

- ▶ Supplied in standard 10 metre length, compressed to 0.6 metre
- ▶ Individually boxed
- ▶ Easy to connect to either round or oval ducting
- ▶ No special tools required for cutting or fixing
- ▶ In the event of a fire, no toxic gases are emitted
- ▶ The products have been successfully fire resistance tested to BS476 parts 6, 7 and 20.

Technical data	
Construction material	Reinforced Aluminium/ Polyester
Wirepitch	24mm
Diameter range (mm)	80-610
Temperature range	-30/+140
Maximum air velocity	30m/sec
Max. positive working pressure	2500 Pa
Standard length	10 metre
Packing	Individual box of 0.6 metre
Clamping	Lightning Band, Stainless Steel Clamps, Nylon Clamps or Quick Release Clamps

Product codes

Ø100mm, 3m	3133
Ø100mm, 6m	3136
Ø125mm, 3m	5133
Ø125mm, 6m	5136
Ø125mm, 10m	51310
Ø150mm, 3m	6133
Ø150mm, 6m	6136

**YOUR
VENTILATION
SPECIALIST**

03443 715 523

www.domusventilation.co.uk

🔍 domusventilation_



©Domus Ventilation 2022. Issue date 2022-08

The information contained in this publication is correct at the time of print and is subject to change. Please visit our website for the latest information: www.domusventilation.co.uk

Domus Ventilation | Block C, Van Court, Caerphilly CF83 3ED, United Kingdom