

# RECTANGULAR FLEXIBLE PVC HOSE

## TECHNICAL DATA SHEET




Domus Ventilation Flexible Hose is a range of wire reinforced, flexible PVC ducting that has been specially designed for the ventilation market. The hose provides solutions to overcome situations where a rigid component cannot be installed.

Flexible hose is particularly suitable for installation where there is slow moving air, such as the ducting of tumble driers.

### CONSTRUCTION

The Flexible Hose is constructed as a continuous left-hand helix (English wound) on a bespoke forming "head". The reinforcing wire is 100% sealed inside a fold of PVC tape which is in turn overlapped by the next pitch. The joints are welded by hot air welding of the layers of PVC in order to produce a continuous sealed tube.

### PRODUCT CODES



Code	Connection
Hose - 0.5m	
3305	Female
Hose - 3m	
333	Female

Code	Connection
Hose - 0.5m	
5305	Female
Hose - 3m	
533	Female

Code	Connection
Hose - 0.5m	
9305	Female
Hose - 3m	
933	Female

**YOUR VENTILATION SPECIALIST**

**03443 715 523**

[www.domusventilation.co.uk](http://www.domusventilation.co.uk)



Technical data	
Material	White PVC 70µm thick
Diameter range (mm)(internal)	110x54, 204x60, 220x90
Temperature range (°C)	-20/+60 working (80 max.)
Standard length (m)	0.5, 3
Packing	Compressed individually in net sleeve
Clamping	D-TIE Nylon zip-tie

©Domus Ventilation 2022. Issue date 2022-08

The information contained in this publication is correct at the time of print and is subject to change. Please visit our website for the latest information: [www.domusventilation.co.uk](http://www.domusventilation.co.uk)

E & OE We reserve the right to alter product specification without prior notice  
**Domus Ventilation** | Block C, Van Court, Caerphilly CF83 3ED, United Kingdom